

PKCELL ER26500 C 3.6v 9000mAh LI-SOCL2 Battery Manufacturer

PKCELL

PKCELL

PKCELL



Typical Huge Applications:

Alarms and security systems, GPS, metering systems, memory back up, tracking system and GSM communication, Aerospace, Defence, Military, Power Management, Portable Devices, Consumer Electronics, Real-time clock, Tracking system, Utility metering, etc.

Specification of ER 26500

Model name: ER26500	Size: C, $\Phi 26.2\text{mm} \times 50.0\text{mm}$ (Max)
Nominal voltage: 3.6V	Nominal capacity: 9000mAh(9Ah)
Open circuit voltage: 3.66V	Cut-off Voltage: 2.0V
Operating temperature range: -55°C to 85°C	Typical weight: 55g
Max Pulse Discharge current: 400mA	Max Continuous Discharge current: 200mA
Standard Current :2.0mA	Typical Shelf life: 10 years

Available Terminations: 1) Standard terminations 2) Solder tabs 3) Axial Pins 4) or special requirement (wire, connectors, etc)

Li-SOCL2(Energy Type) Specifications							
Model IEC		Nominal Voltage(V)	Dimensions (mm)	Nominal Capacity (mAh)	Standard Current (mA)	Max Continuous Discharge Current (mA)	M D Cu
ER10450	AAA	3.6	10.0×45.0	800	1.00	10	
ER14250	1/2AA	3.6	14.5×25.0	1200	0.50	50	

ER14335	2/3AA	3.6	14.5×33.5	1650	0.70	50	
ER14505	AA	3.6	14.5×50.5	2400	1.00	100	
ER17335		3.6	17×33.5	2100	1.00	50	
ER17505		3.6	17×50.5	3400	1.00	100	
ER18505	A	3.6	18.5×50.5	4000	1.00	100	
ER26500	C	3.6	26.2×50.5	8500	2.00	200	
ER34615	D	3.6	34.2×61.5	19000	3.00	200	
ER9V	9V	10.8	48.8×17.8×7.5	1200	1.00	50	
ER261020		3.6	26.5×105	16000	3.00	200	
ER341245		3.6	34×124.5	35000	5.00	400	

Product

link :

<https://www.pkcellpower.com/pkcell-3-6v-c-size-battery-8500mah-lithium-battery-er26500-for-meter-equipement-product/>