

PKCELL CR34615 3V 12000mAh LI-MnO2 Battery Supplier

PKCELL

PKCELL

PKCELL



Applications:

1. Memory backup: CMOS memory, RTC(real time clock) and computer backup.
2. AMR utility meters: Electricity meter, gas meter and water meter etc.
3. Wireless alarm sensors: Smoke alarm systems, temperature monitors etc.
4. Remote monitor systems: GPS, sea buoys, lifejacket lights, lifecraft lights, cargo-locating systems etc.
5. Automotive and electronics: Automotive security systems, tire-pressure monitoring systems etc.
6. Electronics toll tags: Toll gates.
7. Military electronics: Radio communication, night vision equipment, tracking and positioning systems etc.

Advantages:

1. High energy density
2. High open circuit voltage
3. Wide range of operating temperature
4. Stable operating voltage and current
5. Long operating time
6. Low self-discharge rate (less than 1% per year at 25oC)

Cylindrical LiMnO2 Battery							
Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Standard Discharge current(mA)	End Voltage (V)	Max. Diameter (mm)	Max. Height (mm)	Reference Weight (g)
CR17345(CR123A)	3v	1500.0	10	2	17.0	34.5	16
CR15H270(CR2)	3v	850.0	10	2	15.6	27.0	11
CR17335	3v	1500.0	10	2	17.0	33.5	16
CR14250	3v	650.0	10	2	14.5	25.0	10

CR14505	3v	1400.0	10	2	14.5	50.5	17
CR14335	3v	800.0	10	2	14.5	33.5	13
CR17450	3v	2000.0	10	2	17.0	45.0	25
CR17450	3v	2400.0	10	2	17.0	45.0	25
CR17505	3v	2300.0	10	2	17.0	50.5	28
CR17505	3v	2700.0	10	2	17.0	50.5	28
CR18505	3v	2500	10	2	18.5	50.5	35
CR11108(CR1/3N)	3v	160.0	1	2	11.6	10.8	3.3
CR-V3	6v	3000.0	20	2	29X14.5X52		34
CR9V	9v	1200	1	5.4v	48.5X36.5X17.5		29
CR26500	3v	5400	10	2	26.5	50.5	62
CR34615	3v	12000	10	2	34	61.5	125
CR-P2	6v	1400.0	10	4	34.8X35.8X19.5		34
2CR5	6v	1400.0	10	4	34X45X17		34

Product

link : <https://www.pkcellpower.com/pkcell-cr34615-3v-12000mah-li-mno2-battery-product/>